

Data Sheet

Product name: cartridge L-AK 045
 Article number: 400 270.DE.001.002

Product description:

Cartridge L for filtering potable water.

Cartridge L is equipped with a activated carbon block.

Cartridge L is not intended for continuous pressure and may only be used as a flowing water filter.

If the cartridge is to be installed on water pipes, it is recommended to install a check valve in the supply line.

Professional installation must be carried out by a specialist company.

For not professional installation no guarantee is taken over.

Technical data:

outer diameter: approx. Ø 112 mm (measured by the largest measure)

total height: approx. 288 mm

Weight (packed): approx. 780 g

Colour: nature / black (more colours on demand)

Material: PP / POM

Filter medium: actived carbon

Operating life: 1 x internal screw thread $\frac{3}{4}$, 1 x external screw thread $\frac{3}{4}$

The cartridge L-AK 045 must be replaced after max. 6 months or max. 5.000 litres of cold water. Earlier replacement may be necessary if the water flow through the device is noticeably reduced. This is generally an indication of the increased presence of fine particles in the unfiltered water.

Earlier replacement may be necessary if the water flow through the device is noticeably reduced. This is generally an indication of the increased presence of fine particles in the unfiltered water.

Use: Only for cold water up to max. 25°C.

Note: Before first use, expire min. 2-3 litres of cold water, unused.

If you have not used the cartridge L-AK 045 for an extended period, which was in the filter, expire the unused water.

The screw cover on the Cartridge L-AK 045 can be opened, allowing the filter cartridge inside to be replaced. To ensure that the new filter cartridge is installed correctly, we recommend having it installed by a specialist company.

Please use a new sealing ring every time after opening and closing the cartridge L-AK 045.

No liability is accepted for filter cartridges that are not correctly installed. Protect cartridge L-AK 045 against frost.

Comments: The purpose for which our products are used is at the purchaser's sole discretion. We recommend carrying out appropriate trials to test their suitability. All details of measurements and capacities are approximate. Subject to change without notice.

Last revised 12.06.2017



Data Sheet

Product name: cartridge L-VF 01
 Article number: 400 270.DE.001.001

Product description:

Cartridge L for filtering potable water.

Cartridge L is equipped with a activated carbon.

Cartridge L is not intended for continuous pressure and may only be used as a flowing water filter.

If the cartridge is to be installed on water pipes, it is recommended to install a check valve in the supply line.

Professional installation must be carried out by a specialist company.

For not professional installation no guarantee is taken over.

Technical data:

outer diameter: approx. Ø 112 mm (measured by the largest measure)

total height: approx. 288 mm

Weight (packed): approx. 520 g

Colour: nature / black (more colours on demand)

Material: PP / POM

Filter medium: actived carbon and membrane filter

Operating life: 1 x internal screw thread $\frac{3}{4}$, 1 x external screw thread $\frac{3}{4}$



The cartridge L-VF 01 must be replaced after max. 6 months or max. 5.000 litres of cold water. Earlier replacement may be necessary if the water flow through the device is noticeably reduced. This is generally an indication of the increased presence of fine particles in the unfiltered water.

Earlier replacement may be necessary if the water flow through the device is noticeably reduced. This is generally an indication of the increased presence of fine particles in the unfiltered water.

Use: Only for cold water up to max. 25°C.

Note: Before first use, expire min. 2-3 litres of cold water, unused.

If you have not used the cartridge L-AK 045 for an extended period, which was in the filter, expire the unused water.

The screw cover on the Cartridge L-AK 045 can be opened, allowing the filter cartridge inside to be replaced. To ensure that the new filter cartridge is installed correctly, we recommend having it installed by a specialist company.

Please use a new sealing ring every time after opening and closing the cartridge L-VF 01.

No liability is accepted for filter cartridges that are not correctly installed. Protect the cartridge L-VF 01 against frost.

Comments: The purpose for which our products are used is at the purchaser's sole discretion. We recommend carrying out appropriate trials to test their suitability. All details of measurements and capacities are approximate. Subject to change without notice.

Last revised 12.06.2017

Data Sheet

Product name: cartridge L-MAK 015
 Article number: 400 270.DE.001.003

Product description:

Cartridge L for filtering potable water.

Cartridge L is equipped with a activated carbon.

Cartridge L is not intended for continuous pressure and may only be used as a flowing water filter.

If the cartridge is to be installed on water pipes, it is recommended to install a check valve in the supply line.

Professional installation must be carried out by a specialist company.

For not professional installation no guarantee is taken over.

Technical data:

outer diameter: approx. Ø 112 mm (measured by the largest measure)

total height: approx. 288 mm

Weight (packed): approx. 770 g

Colour: nature / black (more colours on demand)

Material: PP / POM

Filter medium: actived carbon and membran filter

Operating life: 1 x internal screw thread $\frac{3}{4}$, 1 x external screw thread $\frac{3}{4}$

The cartridge L-MAK 015 must be replaced after max. 6 months or max. 5.000 litres of cold water. Earlier replacement may be necessary if the water flow through the device is noticeably reduced. This is generally an indication of the increased presence of fine particles in the unfiltered water.

Earlier replacement may be necessary if the water flow through the device is noticeably reduced. This is generally an indication of the increased presence of fine particles in the unfiltered water.

Use: Only for cold water up to max. 25°C.

Note: Before first use, expire min. 2-3 litres of cold water, unused.

If you have not used the cartridge L-AK 045 for an extended period, which was in the filter, expire the unused water.

The screw cover on the Cartridge L-AK 045 can be opened, allowing the filter cartridge inside to be replaced. To ensure that the new filter cartridge is installed correctly, we recommend having it installed by a specialist company.

Please use a new sealing ring every time after opening and closing the cartridge L-MAK 015.

No liability is accepted for filter cartridges that are not correctly installed. Protect the cartridge L-MAK 015 against frost.

Comments: The purpose for which our products are used is at the purchaser's sole discretion. We recommend carrying out appropriate trials to test their suitability. All details of measurements and capacities are approximate. Subject to change without notice.

Last revised 12.0

